

# Installation Checklist

Hydro-Action® AP Series aerobic treatment systems should be serviced at least every six months per NSF requirements. Please consult the Installation Manual while performing this checklist.

- Chose site and soil condition, excavate.  
notes: \_\_\_\_\_
- Install gradeable material and level system.  
notes: \_\_\_\_\_
- Fill tanks with water and leak check while burying.  
notes: \_\_\_\_\_
- Connect inlet and discharge piping.  
notes: \_\_\_\_\_
- Install OPS® as per instructions and run power conduit.  
notes: \_\_\_\_\_
- Inspect diffuser assemblies.  
notes: \_\_\_\_\_
- Install OPS® and Tank Covers w/ supplied security screws.  
notes: \_\_\_\_\_
- Follow start-up procedure and educate homeowner on their system.  
notes: \_\_\_\_\_
- Perform system check to insure proper operation.  
notes: \_\_\_\_\_
- Fill out installation / warranty sheet.  
notes: \_\_\_\_\_
- Give copy of homeowners manual to homeowner.  
notes: \_\_\_\_\_
- Give homeowner copy of service contract and warranty sheet.  
notes: \_\_\_\_\_
- Send in installation warranty sheet to Manufacturer.  
notes: \_\_\_\_\_